


PROPLATE

PROPLATE is a flat joint-cover profile with special profiled edges for perfect adherence to flooring. Made in stainless steel 1.4016 with a protective film and available with or without adhesive or for certain widths also in the punched version. Available in widths of 20 – 30 - 40 – 60 – 80 mm with protective film.

POLISHED STAINLESS 1.4016 STEEL SELF-ADHESIVE OR PUNCHED



EXAMPLES AND INSTRUCTIONS FOR LAYING METHODS




1. Choose "PROPLATE" in the required width and material and whether punched or with self-adhesive backing. 2. Cut the profile to the required length. When laying the self-adhesive Proplate, clean, degrease and dry the surface, checking that the temperature for application is at least 15°. 3. Remove the protective paper from the adhesive and lay the profile correctly applying a uniform vertical pressure by hand without moving the profile and without using iron/steel hammers. 4. When laying the punched version, align the profile as reference. 5. Insert suitable screw anchors (usually Ø 3mm screws & \$x25mm screw anchors). A lign the profile and tighten the galvanised or brassed flathead screws.

PROPLATE

POLISHED BRASS SELF-ADHESIVE OR PUNCHED

EXAMPLES AND INSTRUCTIONS FOR LAYING METHODS



1. Choose "PROPLATE" in the required width and material and whether punched or with self-adhesive backing. 2. Cut the profile to the required length. When laying the self-adhesive Proplate, clean, degrease and dry the surface, checking that the temperature for application is at least 15°. 3. Remove the protective paper from the adhesive and lay the profile correctly applying a uniform vertical pressure by hand without moving the profile and without using iron/steel hammers. 4. When laying the punched version, align the profile and mark the position of the holes using the holes in the profile as reference. 5. Insert suitable screw anchors (usually Ø 3mm screws & 5x25mm screw anchors) 6. Align the profile and tighten the galvanised or brassed flathead screws.

COLOURS

	And other lists in the
OL - Polished brass	



POLISHED STAINLESS 1.4016 ST. thermo packed - ADHESIVE bar length 2,70 lm - pack. 20 Pcs - 54 lm (L 20 - 30mm - 108 lm) - 10/10 mm

Article	Width	
PETAC 20A	20mm	
PETAC 30A	30mm	
PETAC 40A	40mm	
PETAC 60A	60mm	
PETAC 80A	80mm	

POLISHED STAINLESS 1.4016 STEEL thermo packed - without holes bar length 2,70 lm - pack. 20 Pcs - 54 lm- 10/10 mm

Article	Width		
PETAC 60	60mm		
PETAC 80	80mm		
PETAC 60A/80A/60/80, wi	ith 12/10 thicknes	s available o	n demand.

PUNCHED POLISHED STAINLESS 1.4016 ST. with protective film bar length 2,70 Im- pack. 20 Pcs - 54 Im (L 30mm - 108 Im) - 10/10 mm

bai iciigui 2,70 iii - pack. 20	1 C3 - 34 IIII (L 30II	iiii - 100 iiii)	- 10/ 1
Article	Width		
PETAC 30F	30mm		
PETAC 40F	40mm		



POLISHED STAINLESS 1.4016 ST. thermo packed ADHESIVE bar length 0,93 lm- pack. 20 Pcs - 10/10 mm		
Article	Width	
PETAC 309AS	30mm	
PETAC 609AS	60mm	
PETAC 809AS	80mm	

POLISHED STAINLESS 1.4016 ST. thermo packed - SELF PUNCHED WITH SCREWS bar length 0,93 Im- pack. 20 Pcs - 10/10 mm

Article	Width	
PETAC 309FS	30mm	

COLOURS



PROPLATE is a flat joint-cover profile with special profiled edges for perfect adherence to flooring. Made in polished brass with a protective film and available with or without adhesive or for certain widths also in the punched version. Available in widths of 20 - 30 - 40 - 60 - 80 mm with protective film.



POLISHED BRASS thermo packed ADHESIVE bar length 2,70 Im - pack. 20 Pcs - 54 Im (L 20/30mm - 108 Im) - 10/10 mm

bui lengui L, i o ini puen. Lo i es	54 mm (E 20/ 50mm	 10/ 10 11111
Article	Width	
PETOL 20A	20mm	
PETOL 30A	30mm	
PETOL 40A	40mm	
PETOL 60A	60mm	
PETOL 80A	80mm	

POLISHED BRASS thermo packed WITHOUT HOLES bar length 2,70 lm - pack. 20 Pcs - 54 lm (L 20 mm - 108 lm) - 10/10 mm

Article	Width	
PETOL 20	20mm	
PETOL 60	60mm	
PETOL 80	80mm	

PETOL 60A/80A/60/80 with 13/10 thickness available on demand.

POLISHED BRASS with protective film PUNCHED

PETOL 30F

PETOL 40F

bar length 2,70 lm - pack. 20 Pcs - 54 lm (L 30 mm - 108 lm) - 10/10 mm Article Width

30mm

40mm

POLISHED BRASS thermo packed bar length 0,83 lm - pack. 20 Pcs - 1			SELF PACK	
Article	Width			
PETOL 308AS	30mm			*
PETOL 408AS	40mm			*
POLISHED BRASS thermo packed bar length 0,93 Im - pack. 20 Pcs - 10			SELF PACK	
Article	Width			
PETOL 309AS	30mm			
PETOL 309FS	30mm			
PETOL 409AS	40mm			
PETOL 409FS	40mm			*
PETOL 609AS	60mm			*
PETOL 809AS	80mm			*
"AS" at the end of the product code	e = Item with adh	esive		

"FS" at the end of the product code = Punched Item

idth	
mm	
mm	
mm	
	mm

"FS" at the end of the product code = Punched Item

	SELF PACK
Width	
30mm	*
40mm	*
	30mm

***** = Production on demand with minimum quantity of 100 pcs. Production delay 4/5 weeks. Price to be agreed

4



94