
PROTERMSTEP ACC

POLISHED, BRUSHED STAINLESS STEEL AISI 304/1.4301-V2A



EXAMPLES OF LAYING for instructions see the product below





POLISHED STAINLESS STEEL AISI 304/1.4301-V2A with protective film bar length 2,7 lm - pack. 15 Pcs - 40,5 lm

	•			
Article	h / H mm			
PTSPAC 0815	08 / 15			
PTSPAC 10125	10 / 12,5			
PTSPAC 1530	15 / 30			
PTSPAC 2025	20 / 25			
EXTERNAL CORNERS - pack	10 Pcs			
Article	h / H mm			
REPTSAC 0815/10	08 / 15			
REPTSAC 10125/10	10 / 12,5			
REPTSAC 1530/10	15 / 30			
REPTSAC 2025/10	20 / 25			
JUNCTION H 10 - 12,5 - 15 - 20 mm - pack. 10 Pcs				
Article	h/Hmm			
GIPTSAC 0815/10	08 / 15			
GIPTSAC 10125/10	10 / 12,5			
GIPTSAC 1530/10	15 / 30			
GIPTSAC 2025/10	20 / 25			



BRUSHED STAINLESS ST. AISI 304/1.4301-V2A bar length 2,7 lm - pack. 15 Pcs - 40,5 lm

υ.			
Articl	e	h / H mm	
PTSPACS 0815	;	08 / 15	
PTSPACS 1012	:5	10 / 12,5	
PTSPACS 1530)	15 / 30	
PTSPACS 2025	;	20 / 25	
COLOURS			

AC - Polished stainless st. AISI 304/1 4301-V2A 304/1 4301-V2A		ON DEMAND
	AC - Polished stainless st. AISI 304/1.4301-V2A	ACS - Brushed stainless st. AISI 304/1.4301-V2A

JOINT GIPTSAC ..

EXTERNAL CORNER (WELDED)



REPTSAC

SUITABLE FOR USE IN CONTACT WITH FOODSTUFFS PROTERMSTEP ALL is the new step cover profile made of natural and anodized aluminium. Designed to protect

the edge of the step and to hide the joint between the tread and the step rise. The special notched shape in the


PROTERMSTEP ACC is the new step cover profile made of stainless steel. Designed to protect the edge of the step

and to hide the joint between the tread and the step rise. The special notched shape in the upright stem provides it with excellent anchorage between floor/glue/profile. Reversible profile.

PROTERMSTEP ALL

NATURAL AND ANODIZED SILVER ALUMINIUM

PTSPAN/AA 08 PTSPAN/AA 10 H 8 mm H 10 mm 10 mm 10 m PTSPAN/AA 125 PTSPAN/AA 15 H 12,5 mm



H 15 mm 10 mm


EXAMPLES AND INSTRUCTIONS FOR LAYING METHODS





NATURAL ALUMINIUM bar length 2,7 Im - pack. 20 Pcs - 54 Im			
Article	H mm		
PTSPAN 08	8		
PTSPAN 10	10		
PTSPAN 125	12,5		
PTSPAN 15	15		

1. Choose the PROTERMSTEP in the required width and colour according to the thickness of the tile (stairs). **2.** First fix the riser part, placing it at the correct and final height. **3.** Fill the empty spaces under the profile with the tile adhesive. **4.** Apply the adhesive to the tread, lay the profile with the punched base fully sunk into the adhesive and align the profile so that its lip covers the edge of the riser tile. **5.** Lay the tread tiles, aligning them so that they are flush with the upper and rear part of the profile and filling the internal part with adhesive.




ANODIZED SILVER ALUMINIUM thermo packed bar length 2,7 lm - pack. 20 Pcs - 54 lm

Article	H mm	
PTSPAA 08	8	
PTSPAA 10	10	
PTSPAA 125	12,5	
PTSPAA 15	15	

COLOURS

AN - Natural aluminium AA - Anodized silver aluminium





upright stem provides it with excellent anchorage between floor/glue/profile.

POGRESS ΤL Е

130