

It is an uncoupling and waterproofing membrane for problematic substrates, balconies, terraces and horizontal surfaces of any size without expansion joints in the screed before the laying of ceramic and natural stone. **PRODESO®** ensures the laying of the flooring and the waterproofing of the substrate also in case of old tiles, on cracked and not perfectly cured substrates, and therefore with possible vapour pressure.

PRODESO® MEMBRANE

UNCOUPLING & WATERPROOFING
MEMBRANE

PRODESO® MEMBRANE

Article	H roll (m)	L roll (m)	Thickness (mm)	Rolls/Pallet		
PDES 3530/EN	1	30	3,5	8		
PDES 3505/EN	1	5	3,5	56		

WHY USE PRODESO® MEMBRANE SYSTEM


Time Efficient: PRODESO® Membrane reduces drastically the installation times because from the installation of the membrane up to the laying of flooring you can work without interruption.

Flexible: it is suitable for every types of subfloor including very large surfaces both indoor and outdoor.

Safe: it is suitable for substrates with cracks as it does not transmit tension of the substrate to the tile coverings and vice versa. It is also suitable on substrates not perfectly cured since it allows the vapour management.

WARNINGS

Do not lay tiles with a size less than 5 x 5 cm. The technical and application details can be found in the **PRODESO® MEMBRANE SYSTEM** brochure. For other informations not described in the brochure **PRODESO® MEMBRANE SYSTEM**, refer to the technical department.



PROBAND 150/250 is a waterproofing polyethylene tape with nonwoven polypropylene fabric on both side that guarantees high adhesion to the support.

PROBAND 150/250

ROLLS IN HDPE AND PP

PROBAND 150/250

Article	H roll (m)	L roll (m)	Thickness (mm)	Rolls/Pallet		
PRBPE 1507	150	7,5	0,42	16		
PRBPE 1530	150	30	0,42	6		
PRBPE 2530	250	30	0,42	3		

For the indicative consumption of proband koll AB during the installation of the **PROBAND**, consult the technical data sheet of **PROBAND 150/250**



AREA OF USE

- **Use** - Terraces, balconies and outside surfaces of any dimension, bathrooms, showers, swimming pools and tanks. To realize waterproofing joints between floor and wall and along two adjacent rolls of **PROFOIL**, **PRODESO® MEMBRANE SYSTEM** and **PRODESO® HEAT/GRIP SYSTEM**
- **Don't use** - On bituminous coverings, over thermal-insulating layer and lightweight screed. With adhesives containing solvents.

WARNINGS

Store in a cool and dry place avoiding direct sunlight and sources of heat. Read the data sheet before applying; in case of special applications call the technical department

RECOMMENDED ADHESIVES FOR THE LAYING OF PRODESO® MEMBRANE (grey color)

 H40 NO LIMITS H40 REVOLUTION H40 EXTREME	 SUPERFLEX K77 POWERFLEX K50 LITOSTONE K99	 FLEXBOND C2S1 FLEXBOND LIGHT C2S1 WETBOND RAPID C2F	 GRIGOKOLL TEX GRIGOKOLL MAX GRIGOKOLL VELOX	 CERAM 255 STARFLEX CERAM 255 EASY S1 CERAM 270 MULTIFLOW	 ULTRAGRES 400 ULTRAGRES FLEX ULTRAGRES FAST	 Für Bau-Profis PERICOL R-FLEX PERICOL EXTRA FLEX PERICOL FLEX	 KEDIFLEX S1 KEDYTOP FAST MAXI
 335 MAXI S 335 SUPER FLEX 325 RAPID FL	 ARDEX X 78 ARDEX X 90 OUTDOOR ARDEX AF 495	 MUREFLEX MFK 45 ADESIVO FBS 75 MAXIMO M 41	 RT UNIVERSAL RT HI TECH RT RAPID FLEX	 SEYFLEX S1 SEYULTRA T TIXOSEY	 KRISTAL C2TE EXTRA C2S1	 AZ 59 RAPID MAXI SPECIAL ONE	 CERMIPLUS 2.0 CERMIPLUS XL FLEX 2.0
 NEOFIL F10 TECH S1 SILIKOLL FLEX S1 NEOFIL F50 RAPID	 FORTEM MAXIM	 BENFERFLEX+S1 BENFERFLEX C2 BENFERFLEX + FAST-S1	 F.55 CERMONO PLUS F.55 CERFIX F.55 CERMONO RAPIDO	 EXTRA 30 MAXI ADEFLEX GREEN S1 EXTRA 30 POWER	 POWER CX 3 POWER CX 7 POWER RX 6 TURBO	 KERAFLEX EASY ULTRALITE S1 KERAFLEX MAXI S1	