PROSKIRTING LED is an innovative patented baseboard called "cable duct" in anodized aluminium, with illumination led system incorporated. Conceived and designed to illuminate the passage zone such as corridors and house and office entrances as well. It generates soft and indirect light. Moreover, it solves many other problems such as the laying of the baseboard itself, the passage of the electric cables, the ones for PC, telephone and other plants as well. **PROSKIRTING LED** has been designed with double function and utility: 1- **PROSKIRTING LED** complete PKLEDAA 80 is an inspectional joint baseboard composed of PKGS 66 support for fixing it with screws on the wall and the **PROSKIRTING LED** PKLEDAA 80 is a sight profile. 2- **PROSKIRTING LED** PKLEDAA 80 is a stight baseboard profile to be fixed directly wtth silicone/ adhesive. It is not an inspectional one like **PROSKIRTING LED** complete, and is available also in auto adhesive version (PKLEDAA 80A).

PROSKIRTING

ANODIZED SILVER ALUMINIUM WITH LED AND POWER SUPPLY BOX



SKIRTING BOARD IN ANOD. SILVER ALU. WITHOUT ADHESIVE. ADAPTOR LED, LED & FLAT NOT INCLUDED (indicate the article)

thermo pacted barrengar 2 mil	pack. 10 1 CS ZO IIII
Article	H mm
PKLEDAA 80	80

SKIRTING BOARD IN ANOD. SILVER ALUM, WITH ADHESIVE. ADAPTOR LED, LED & FLAT NOT INCLUDED (indicate the article) thermo packed - bar length 2 lm - pack. 10 Pcs - 20 lm

Article	H mm	
PKLEDAA 80A	80	*

Please, specify in your order the code of the FLAT you choose: matt or gloss. Eg.: PKLEDAA 80 + PKGPIAL



ADHESIVE FLEXIBLE LED COIL

Articl	e	
LEDN		
LEDF		
LEDC		

ALL 7512

"F" at the end of the product code = cold light "C" at the end of the product code = hot light



POWER SUPPLY BOX SOCKET with FASTENING BASIS

Article	
SPA 1820	







CABLE RACEWAY/ SUPPORT- COEXTRUDED PVC

Jai leligui Z IIII - pack. ZU F	C3 - 40 IIII	
Article	H mm	
CSPPK 80	70	

PUNCHED SUPPORT - NATURAL ALUMINIUM support length 2 cm - pack. 10 Pcs

Article H mm PKGS 66 66

ARTICLES NOT FOR SALE SINGLY



COLOURS



On demand may be realised in other finishes of the colour chart. Contact our customer service for minimum quantity, timing and price.









with FASTENING BASIS

IUNCTION BOX

SWITCH BOX


SD 1210




PSPV

It matches with CSPPK 80.

PKLEDAA 80 / PKLEDAA 80A



EXAMPLES AND INSTRUCTIONS FOR LAYING METHODS






1. Fix the support one the wall putting the screws and plugs every 50 cm (recommended). Make a test with "PROSKIRTING LED" in order to value the height and the correct position of supports. 2. Fix in the chosen spaces the socket/ power supply box basis, switch box basis and, eventually, the junction box. 3. Connect 220V supply to power/ transformer unit, and afterwards, connect the "PROSKIRTING LED" bar next to power unit. 4. Connect the pre-applied led bars inside the "PROSKIRTING LED" with the supplied cables/ wires in continuous way. **5**. The power supply unit guarantees about 15 lm of led illumination, beyond that distance it is necessary to add another power supply box/socket. When fixing without support, clean the surface carefully so that it's

dry and with no grass trace, apply the silicone on the knurled sides of the profile and lay down correctly, pressing uniformly and with no hammering. For the application of "PROSKIRTING LED" with adhesive, we recommend the temperature not below 15°

CORNERS, END CAPS and JOINTS

VARNISHED PLASTIC SILVER FINISH



IN/EXTERNAL CORNER - VARNISHED PLASTIC (SILVER FIN.)

pack. 3 PCS		
Article	HxLmm	
PKAGI 80/5	80 X 40	
PKAGE 80/5	80 X 40	

JOINTS - VARNISHED PLASTIC (SILVER FIN.) - pack. 10 Pcs

Article	H mm	
PKGIN 80/10	80	

END CAPS R / L - VARNISHED PLASTIC (SILVER FIN.)

Article		H mm	
PKTDSAA 80/5	8	0	









