SKIRTING 40 made in anodized, polished and brushed aluminium in height 40 mm. Available with or without adhesive. Superior aesthetic quality and easy to lay, it is ideal for all public and private environments. Can be used with all types of flooring. In order to facilitate and to perfect the laying process, internal and external angles, plugs and junctions are recommended.

Please contact the technical department for informations concerning the skirting bending radius.

SKIRTING 40

ANODIZED, POLISHED, VARNISHED and BRUSHED ALUMINIUM



ANODIZED SILVER ALUMINIUM thermo packed

bar length 2 lm - pack. 40 Pcs - 80 lm

Article	H mm		
BTAA 40A	40		
BTAA 40	40		
"A" at the end of the product cod	la = Itam with	n adhasiva	

POLISHED TITANIUM ALUMINIUM thermo packed

bar length 2 lm - pack. 40 Pcs - 80 lm

Article	H mm		
BTBT 40A	40		
BTBT 40	40		
"A" at the end of the product coo	de = Item witl	n adhesive	

VARNISHED SEMIGLOSSY AND MATT WHITE ALUMINIUM

thermo packed - bar length 2 lm - pack. 40 Pcs - 80 lm H mm BTA 40-01A 40 BTA 40-01 40

40

40

"A" at the end of the product code = Item with adhesive



BRUSHED ALUMINIUM (silver-copper-titanium)

thermo packed - bar length 2 lm - pack. 40 Pcs - 80 lm

Article	H mm	
BTBS 40A	40	
BTBS 40	40	
BTRS 40A	40	
BTRS 40	40	
BTTS 40A	40	
BTTS 40	40	

"A" at the end of the product code = Item with adhesive

STONE LINE ALUMINIUM

thermo packed - bar length 2 lm - pack. 40 Pcs - 80 lm


Article	H mm	
BTA 40-SL02A	40	
BTA 40-SL02	40	
BTA 40-SL03A	40	
BTA 40-SL03	40	
BTA 40-SL04A	40	
BTA 40-SL04	40	
0.4.0	the second second	

"A" at the end of the product code = Item with adhesive



BT... 40/40A

EXAMPLES AND INSTRUCTIONS FOR LAYING METHODS



1. Choose the "SKIRTING 40" also choose with or without adhesive. Cut the profile to the required length, taking care to calculate the width of the inside-outside corner joints.
For the self-adhesive version, the surface must be smooth, grease-free and not porous.
It is not recommended for plaster and mortar surfaces (version) without adhesive is better, using fast-setting acrylic silicone which is suitable for fixing aluminium to mortar - plaster, etc.). 4. Use the corner linking elements-joints and right and left end caps to facilitate laying.

COLOURS

BTA 40-010A

BTA 40-010

ANODIZED	POLISHED	BRUSHED		
			ON DEMAND	
AA - Anodized silver alum.	BT - Polished titanium alum.	BS - Brushed silver alum.	RS - Brushed copper alum.	TS - Brushed titanium alur
SEMIGLOSSY				
SEWIGLOSSY	MATT		STONE LINE	
SEMIGLOSSY	ON DEMAND	ON DEMAND	ON DEMAND	ON DEMAND

(There aren't combinations for the finish alu. RS)

On demand may be realised in other finishes of the colour chart. Contact our customer service for minimum quantity, timing and price.

USE PROBAND FIX FOR FIXING THE PROFILE TO THE WALL



CORNERS, END CAPS AND JOINTS

VARNISHED METAL and VARNISHED PLASTIC

* Corners, end caps and joints of the on demand profiles are also on demand

INTERNAL/EXTERNAL CORNER - EDGE COVER - VARNISHED METAL. ANODIZED, POLISHED STONE LINE - H 40 MM - L 20 MM

	 	•
Article		
RIZCTAA 40/		
REZCTAA 40/		
RIZCTBT/BS/TS/RS 40/		
REZCTBT/BS/TS/RS 40/		
RIZCT01/01O 40/		
REZCT01/01O 40/		
RIZCTA 40-SL/		
REZCTA 40-SL/		
Chance the decired packaging		

Choose the desired packaging. E.g.: RIZCTAA 40/2 (pack. 2 Pcs) - RIZCTAA 40/5 (pack. 5Pcs)

IOINT - FDGE COVER VARNISHED METAL ANODIZED, POLISHED, STONE LINE

Article	H mm	
GIZCTAA 40/	40	
GIZCTBT/BS/TS/RS 40/	40	
GIZCT01/01O 40/	40	
GIZCTA 40-SL/	40	

END CAPS R / L - EDGE COVER - VARNISHED METAL ANODIZED POLISHED, STONE LINE - pack. 4Pcs (2 R + 2 L) / 10Pcs (5 R + 5 L)

Article	H mm		
TPZCTAA 40/	40		
TPZCTBT/BS/TS/RS 40/	40		
TPZCT01/01O 40/	40		
TP7CTA 40-SI /	40		

METAL EDGE COVER





INTERNAL/EXTERNAL CORNER - FDGE COVER

VARNISHED PLASTIC ANODIZED SILVER, POLISHED AND TITANIUM

Article	HxL mm	
RICTAA 40/	40 x 20	
RECTAA 40/	40 x 20	
RICTBT 40/	40 x 20	
RECTBT 40/	40 x 20	

Choose the desired packaging. E.g.: RICTAA 40/2 (pack. 2 Pcs) - RICTAA 40/5 (pack. 5 Pcs)

Available on demand aluminium prewelded internal and external flush corners. Finishing: 01 - 010 - AA - BT - BS - RS - TS. Price to be agreed. Production delay 4/5 weeks.

IOINT - FDGE COVER

VARNISHED PLASTIC ANODIZED SILVER, POLISHED AND TITANIUM

Article	H mm	
GICTAA 40/	40	
GICTBT 40/	40	

END CAPS R / L - EDGE COVER - VARNISHED PLASTIC ANODIZED SILVER, POLISHED AND TITANIUM - pack. 4Pcs (2 R + 2 L) / 10Pcs (5 R + 5 L)

Article	H mm	
TPCTAA 40/	40	
TPCTBT 40/	40	

Choose the desired packaging. E.g.: TPCTAA 40/2 (pack. 4 Pcs: 2 right + 2 left)



RICT... 40/





RECT... 40/. external corner



