The **CROSS-SHAPED** and **T-SHAPED SPACERS** are perforated, weatherproof and made in top quality material with choice of colour. They are used to provide regular gaps in floors and coverings and thanks to the antifloating perforations remain in the correct laying position. Available in every required thickness 1 - 2 - 3 - 4 - 5 - 7 - 10 mm. Levelling wedges are also available for compensating differences in level that emerge during laying. The **Y-SHAPED SPACERS** have to be used to separate hexagonal tiles in floors and walls. Available in thickness 2 and 3 mm.

SPACERS LEVELLING WEDGES

PERFORATED SPACERS CROSS-SHAPED boxes with bags of 250 Pcs each

TERI ORATED SI ACERS CROSS SHALED BOXES WITH BUSS OF 250 FCS CUCH										



PERFORATED SPACERS T-SHAPED boxes with bags of 250 Pcs each

Article	Thick. mm	Pcs/Box	
RT 1	1	20.000	
RT 2	2	15.000	
RT 3	3	15.000	
RT 4	4	15.000	
RT 5	5	15.000	
RT 7	7	10.000	
RT 10	10	5.000	



Y-SHAPED SPACERS FOR HEXAGONAL TILES boxes with bags of 250 Pcs each

RY 2	2	10.000	
RY 3	3	10.000	








LEVELLING WEDGES boxes with bags of 500 Pcs

Article	Thick. mm	Pcs/Box	
PCU 5	0 - 5	10.000	





SPACERS / SQ.M

TILE FORMAT cm x cm	60 x 60	60 x 30	40 x 40	40 x 30	40 x 20	33 x 33	30 x 30	30 x 20	25 x 25	20 x 20	15 x 15	13 x 26	13 x 13	10 x 20	10 x 10
CROSS-SHAPED SPACERS No. / Sq.m	3	6	7	9	12	9	11	17	16	25	44	30	60	50	100
T-SHAPED SPACERS No. / Sq.m	6	12	14	18	24	18	22	34	32	50	88	60	120	100	200
Y-SHAPED SPACERS	2 spacers for each tile multiplied by the amount of tiles per square meter														